

LINEAR SNACK



La gamma Linear Snack nasce dalla nostra idea di ristorazione moderna.

Rapidità e praticità di utilizzo sono le proprietà progettuali di questi tavoli refrigerati dedicati al "fast food". Cassetti ad estrazione totale e altezza ottimizzata per accogliere moduli per la cottura veloce, uniti a diverse opzioni di piano lavoro, sono le caratteristiche essenziali di un prodotto dal design innovativo.

The Linear Snack range arise from our idea of modern catering.

Rapidity and practicality of use are the design properties of these refrigerated tables dedicated to the "fast food" universe. Total extraction drawers and the optimized height designed to accommodate modules for the fast cooking, combined with different worktop options, are the essential characteristics of this innovative design product.





Vani cassetto con maniglia orizzontale e guarnizioni ad incastro
Drawer compartments with horizontal handle and snap out gasket



Fondo interno arrotondato per una migliore pulizia
Inner bottom panel with rounded corners for easier cleaning



Cassetti con guide ad estrazione totale
Total extraction drawers



Versione con cassetti interi o doppi
Full or mid-size drawers



Versioni con piano lavoro dritto, invaso o senza piano
Versions with straight recessed worktop, or without top



Ruote (optional)
Castors (option)



3D Cooling system
L'unico sistema che garantisce una temperatura corretta ed uniforme in tutti i vani.

3D Cooling system
The only system that guarantees a correct and uniform temperature in the whole counter.



Tavoli refrigerati ventilati su piedi o ruote linea snack, profondità 700mm, altezza corpo H 443mm, in acciaio inox AISI 304; 2 vani GN1/1, con cassetto intero (mod. 1C) o due mezzi cassette (mod. 2C) con guide a estrazione totale.

S/s AISI 304 ventilated refrigerated counters snack line on feet or castors, 700 mm of depth, body height H 443 mm; 2 doors GN 1/1, with full (mod. 1C) or 1/2 drawers (mod. 2C) per door with full extraction drawers.

- Gruppo incorporato
- Piano dritto H 40mm (mod. V)
- Piano invaso (mod.I)
- Senza piano (mod. S)
- Controller digitale
- Interni arrotondati
- Sbrinamento ed evaporazione dell'acqua di condensa automatici.

- Built unit
- Versions with straight worktop H 40mm (mod. V)
- Recessed worktop (mod.I)
- Without top (mod. S)
- Digital controller
- Inner bottom panel with rounded corners
- Automatic systems for defrosting and evaporation of the condensation water.

LINEAR SNACK

702



Modello Model	Codice Code	Piano Worktop	Cassetti Drawers	Range Range	GAS GAS	Classe energetica Energy class	Classe climatica Climate class	Consumo elettrico annuale Annual electricity consumption	Volume utile netto Net storage volume	Dimensioni Dimensions mm	Assorbimento Absorbed power		Voltaggio Voltage Volt/Ph/Hz	Dimensioni imballo Packing dimensions mm	Peso Netto/Lordo Net/Gross weight Kg	
											Watt****	A				
	LINEAR SNACK 702 TN/V 1C	7LS72IP2VA002		Piano dritto Straight worktop H=40 mm	2	-2/+7° C	R290 - GWP 3 - Kg 0,080	D	5 40°C - 40%HR	1364	86,08	120	3.8	230/1/50	1220x705x700	126/141
	LINEAR SNACK 702 BT/V 1C	7LS72IB2VA002		Piano dritto Straight worktop H=40 mm	2	-10/-24° C	R290 - GWP 3 - Kg 0,090	G	5 40°C - 40%HR	3133		353	6.15	230/1/50	1220x705x700	126/141
	LINEAR SNACK 702 TN/I 1C	7LS72IP2IA002		Con piano invaso Recessed worktop	2	-2/+7° C	R290 - GWP 3 - Kg 0,080	D	5 40°C - 40%HR	1364		120	3.8	230/1/50	1220x705x700	126/141
	LINEAR SNACK 702 BT/I 1C	7LS72IB2IA002		Con piano invaso Recessed worktop	2	-10/-24° C	R290 - GWP 3 - Kg 0,090	G	5 40°C - 40%HR	3133		353	6.15	230/1/50	1220x705x700	126/141
	LINEAR SNACK 702 TN/S 1C	7LS72IP2NA002		Senza piano Without worktop	2	-2/+7° C	R290 - GWP 3 - Kg 0,080	D	5 40°C - 40%HR	1364		120	3.8	230/1/50	1220x705x700	126/141
	LINEAR SNACK 702 BT/S 1C	7LS72IB2NA002		Senza piano Without worktop	2	-10/-24° C	R290 - GWP 3 - Kg 0,090	G	5 40°C - 40%HR	3133		353	6.15	230/1/50	1220x705x700	126/141
	LINEAR SNACK 702 TN/V 2C	7LS72IP2VA001		Piano dritto Straight worktop H=40 mm	4	-2/+7° C	R290 - GWP 3 - Kg 0,080	D	5 40°C - 40%HR	1364		120	3.8	230/1/50	1220x705x700	126/141
	LINEAR SNACK 702 BT/V 2C	7LS72IB2VA001		Piano dritto Straight worktop H=40 mm	4	-10/-24° C	R290 - GWP 3 - Kg 0,090	G	5 40°C - 40%HR	3133		353	6.15	230/1/50	1220x705x700	126/141
	LINEAR SNACK 702 TN/I 2C	7LS72IP2IA001		Con piano invaso Recessed worktop	4	-2/+7° C	R290 - GWP 3 - Kg 0,080	D	5 40°C - 40%HR	1364	120	3.8	230/1/50	1220x705x700	126/141	
	LINEAR SNACK 702 BT/I 2C	7LS72IB2IA001		Con piano invaso Recessed worktop	4	-10/-24° C	R290 - GWP 3 - Kg 0,090	G	5 40°C - 40%HR	3133	353	6.15	230/1/50	1220x705x700	126/141	
	LINEAR SNACK 702 TN/S 2C	7LS72IP2NA001		Senza piano Without worktop	4	-2/+7° C	R290 - GWP 3 - Kg 0,080	D	5 40°C - 40%HR	1364	120	3.8	230/1/50	1220x705x700	126/141	
	LINEAR SNACK 702 BT/S 2C	7LS72IB2NA001		Senza piano Without worktop	4	-10/-24° C	R290 - GWP 3 - Kg 0,090	G	5 40°C - 40%HR	3133	353	6.15	230/1/50	1220x705x700	126/141	
KIT 4 RUOTE VERS220-60			Sovrapprezzo per 4 ruote Sovrapprezzo Versione 220V/60Hz			Price increase for 4 castors Price Increase Power supply 220V/60Hz **** Watt TN (-10/+45°C) - Watt BT (-30/+45°C)										

**** Watt TN (-10/+45°C) - Watt BT (-30/+45°C)

I gas fluorurati a effetto serra sono contenuti in apparecchiature ermeticamente sigillate.

Dati tecnici e caratteristiche soggetti a cambiamento senza preavviso.

Fluorinated greenhouse refrigerant gases are contained in hermetically sealed equipment.

All specifications are subject to change without notice.



Tavoli refrigerati ventilati su piedi o ruote linea snack, profondità 700mm, altezza corpo H 443mm, in acciaio inox AISI 304; 3 vani GN1/1, con cassetto intero (mod. 1C) o due mezzi cassette (mod. 2C) con guide a estrazione totale.

S/s AISI 304 ventilated refrigerated counters snack line on feet or castors, 700 mm of depth, body height H 443 mm; 3 doors GN 1/1, with full (mod. 1C) or 1/2 drawers (mod. 2C) per door with full extraction drawers.

- Gruppo incorporato
- Piano dritto H 40mm (mod. V)
- Piano invaso (mod. I)
- Senza piano (mod. S)
- Controller digitale
- Interni arrotondati
- Sbrinamento ed evaporazione dell'acqua di condensa automatici.

- Built unit
- Versions with straight worktop H 40mm (mod. V)
- Recessed worktop (mod. I)
- Without top (mod. S)
- Digital controller
- Inner bottom panel with rounded corners
- Automatic systems for defrosting and evaporation of the condensation water.

LINEAR SNACK

703



Modello Model	Codice Code	Piano Worktop	Cassetti Drawers	Range Range	GAS GAS	Classe energetica Energy class	Classe climatica Climate class	Consumo elettrico annuale Annual electricity consumption	Volume utile netto Net storage volume	Dimensioni Dimensions mm	Assorbimento Absorbed power		Voltaggio Voltage Volt/Ph/Hz	Dimensioni imballo Packing dimensions mm	Peso Netto/Lordo Net/Gross weight Kg	
											Watt****	A				
	LINEARSNACK703TN/V 1C	7LS73IP2VA002	Piano dritto Straight worktop H=40 mm	3	-2/+7° C	R290 - GWP 3 - Kg 0,080	D	5 40°C - 40%HR	1550	129,12	1600X685X613	120	3.8	230/1/50	1620x705x700	136/151
	LINEARSNACK703BT/V 1C	7LS73IB2VA002	Piano dritto Straight worktop H=40 mm	3	-10/-24°C	R290 - GWP 3 - Kg 0,090	G	3560	1600X685X613		120	3.8	230/1/50	1620x705x700	136/151	
	LINEARSNACK703TN/I 1C	7LS73IP2IA002	Con piano invaso Recessed worktop	3	-2/+7° C	R290 - GWP 3 - Kg 0,080	D	1550	1600X685X613		120	3.8	230/1/50	1620x705x700	136/151	
	LINEARSNACK703BT/I 1C	7LS73IB2IA002	Con piano invaso Recessed worktop	3	-10/-24°C	R290 - GWP 3 - Kg 0,090	G	3560	1600X685X613		353	6.15	230/1/50	1620x705x700	136/151	
	LINEARSNACK703TN/S 1C	7LS73IP2NA002	Senza piano Without worktop	3	-2/+7° C	R290 - GWP 3 - Kg 0,080	D	1550	1600X673X572		120	3.8	230/1/50	1620x705x700	136/151	
	LINEARSNACK703BT/S 1C	7LS73IB2NA002	Senza piano Without worktop	3	-10/-24°C	R290 - GWP 3 - Kg 0,090	G	3560	1600X673X572		353	6.15	230/1/50	1620x705x700	136/151	
	LINEARSNACK703TN/V 2C	7LS73IP2VA001	Piano dritto Straight worktop H=40 mm	6	-2/+7° C	R290 - GWP 3 - Kg 0,080	D	1550	1600X685X613		120	3.8	230/1/50	1620x705x700	136/151	
	LINEARSNACK703BT/V 2C	7LS73IB2VA001	Piano dritto Straight worktop H=40 mm	6	-10/-24°C	R290 - GWP 3 - Kg 0,090	G	3560	1600X685X613		353	6.15	230/1/50	1620x705x700	136/151	
	LINEARSNACK703TN/I 2C	7LS73IP2IA001	Con piano invaso Recessed worktop	6	-2/+7° C	R290 - GWP 3 - Kg 0,080	D	1550	1600X685X613	120	3.8	230/1/50	1620x705x700	136/151		
	LINEARSNACK703BT/I 2C	7LS73IB2IA001	Con piano invaso Recessed worktop	6	-10/-24°C	R290 - GWP 3 - Kg 0,090	G	3560	1600X685X613	353	6.15	230/1/50	1620x705x700	136/151		
	LINEARSNACK703TN/S 2C	7LS73IP2NA001	Senza piano Without worktop	6	-2/+7° C	R290 - GWP 3 - Kg 0,080	D	1550	1600X673X572	120	3.8	230/1/50	1620x705x700	136/151		
	LINEARSNACK703BT/S 2C	7LS73IB2NA001	Senza piano Without worktop	6	-10/-24°C	R290 - GWP 3 - Kg 0,090	G	3560	1600X673X572	353	6.15	230/1/50	1620x705x700	136/151		
KIT 4 RUOTE VERS220-60			Sovrapprezzo per 4 ruote Sovrapprezzo Versione 220V/60Hz			Price increase for 4 castors Price Increase Power supply 220V/60Hz **** Watt TN (-10/+45°C) - Watt BT (-30/+45°C)										

**** Watt TN (-10/+45°C) - Watt BT (-30/+45°C)

I gas fluorurati a effetto serra sono contenuti in apparecchiature ermeticamente sigillate.

Dati tecnici e caratteristiche soggetti a cambiamento senza preavviso.

Fluorinated greenhouse refrigerant gases are contained in hermetically sealed equipment.

All specifications are subject to change without notice.



Specialist Suppliers of Blast Chiller/Freezers & Quality Commercial Refrigeration

ABLE

Phone:

08 9242 7521

Head Office:

8 Guthrie Street,
Osborne Park WA 6017

Web:

www.ableproducts.com.au

Email:

sales@ableproducts.com.au

**Exclusive Australian
Agents for AFINOX**